

# OneSystem standard panic lock narrow stile



## Product description

- OneSystem panic lock N16XX according to EN 179 and EN 1125 for tubular frame doors. Approved for fire barriers according to EN 1634 / product-specific environmental product declaration (EPD) according to EN 15804 with article-specific parameters / tested for 200,000 cycles and 300 kg door weight.

## Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Compliance with EN 179/EN 1125, EN 12209
- Small rear backset 15 mm
- Panic function inwards/outwards switchable
- Optional: Bus system with integrated monitoring sensors and simplified connection via 5-wire cable
- Closed lock case
- Latch, reversible between DIN left and right in new design for greater strength and with integrated noise reduction
- Security fittings and oval roses can be screwed on through the lock
- Deadbolt with anti-tampering design
- Optional: Bus System with integrated monitoring function
- Developed for Euro profile cylinder and Swiss round Profile cylinder

## Note

- For U-shaped versions, the end caps are included in the scope of supply. Please note: for U-shaped versions, the backset is shortened by 1mm.
- locks with panic function P are not available with top locking. When ordering a faceplate length of 320mm, the faceplate is extended at the bottom by 50mm.

## Technical data

Mounting	Standard panic lock
Latch	DIN L/R
Monitoring	No
Symmetry	symmetrical
Self-locking system	No
Distance	94 mm
Backset	35 mm
Stulp	U6 x 24 mm
Type of cylinder	Swiss profile cylinder
Suitable for fire doors	Yes
Face plate length	320 mm
Panic function	B
Obenverriegelung door system	Yes
Material faceplate	Stainless steel
Bolt throw	20 mm
Handle follower	9 mm
Article number	N1603400992000F

