



Product description

- The 819N0 is a self-activating lock with multi-point lock with electro-mechanically coupling door handle on the outside and inside for single-leaf doors. It fulfills the requirements for burglary-resistant doors and fire doors, which have no additional emergency exit door or panic door requirements. A mechanical sequence control system reliably prevents unwanted extension of the bolt when the door is open. The lock can be used universally for DL/DR with a universal double action latch and switchable control latch.
- The fail-locked or fail-unlocked operating mode can be switched on the lock. Integrated electronic control device for external triggering or connection to the ASSA ABLOY Hi-O bus System.
- Integrated monitoring functions via contactless sensors for status query via the external OneSystem IO module:
 - Door status via striking plate contact
 - Bolt retracted and bolt extended
 - Cylinder monitoring
 - Handle follower monitoring inside and outside
 - Status handle coupling engaged/disengaged

Overview of Advantages

- Integrated motor coupling for controlling the outer handle
- Integrated electronic control device for external activation without additional control, additional functions via the external OneSystem IO module available as an alternative
- Hi-O bus technology for connection to the ASSA ABLOY Hi-O bus system
- Integrated monitoring functions via contactless sensors for status query via the external OneSystem IO module:
 - Door status via striking plate contact
 - Bolt position retracted and extended
 - Cylinder monitoring
 - Handle follower monitoring outside and inside
 - Handle coupling on or off
 - Uniform connection technology: 2-wire bus technology
 - 6 mm full face plate for added security
 - Uniform lock case dimensions, compatible with 309N/319N (mechanical) and 509N/519N (motor lock)
- Suitable for DIN left/right use thanks to universal double action latch and reversible control latch
- Security fittings and oval roses can be screwed on through the lock
- Panic side outwards or inwards opening, reversible
- Solid, surface-hardened deadbolts with 20 mm throw, transverse shear stress 20,000 N
- One variant for Euro profile cylinder and Swiss round profile cylinder

Note

- Striking plate must be ordered separately.

Technical data

| | |
|---|--|
| Input operating voltage | 12 -24 V DC +/- 15% |
| Rated current consumption | 50 mA (locked in idle state) |
| Stromaufnahme (Kupplung aktiv) | 80 mA (<500ms) |
| Bolt throw | 20 mm |
| Handle follower | 9 mm |
| Material faceplate | Chrome-plated steel |
| Dimension housing | 328 x 20 x Dornmaß + 15,5 mm (L x B x H) |
| Faceplate dimensions | 1760 x 24 x 6 mm |
| Side deadbolt stress according to EN 12209 | 20.000 N |
| Deadbolt counterforce according to EN 12209 | 6.000 N |
| Alternative function | Yes |
| Distance | 94 mm |
| Face plate length | 1760 mm |
| Mounting | Handle-controlled security multi-point lock with continuous handle follower without panic function |
| Panic function | Nein |
| Backset | 65 mm |

Article number 819N00016900000

